

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/17/2021

Reviewed on 10/17/2021

1 Identification

- **Product identifier**
- **Trade name:** E-Benzen
- **CAS Number:**
71-43-2
- **EC number:**
200-753-7
- **Index number:**
601-020-00-8
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Energy Chemical Co. Semnan
No. 60, Golfam St, Africa Ave.
TEHRAN 1915673641
IRAN
- **Information department:** Product safety department.
- **Emergency telephone number:** During normal opening times: +98 21 2205 2178

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 1 H310 Fatal in contact with skin.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/17/2021

Reviewed on 10/17/2021

Trade name: E-Benzen

(Contd. of page 1)

· **Label elements**· **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS02 GHS06 GHS07 GHS08

· **Signal word** *Danger*· **Hazard-determining components of labeling:***benzene*· **Hazard statements***Highly flammable liquid and vapor.**Fatal in contact with skin.**Causes skin irritation.**Causes serious eye irritation.**May cause genetic defects.**May cause cancer.**Causes damage to organs through prolonged or repeated exposure.**May be fatal if swallowed and enters airways.*· **Precautionary statements***Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Keep container tightly closed.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Do not breathe dust/fume/gas/mist/vapors/spray.**Do not get in eyes, on skin, or on clothing.**Wash thoroughly after handling.**Do not eat, drink or smoke when using this product.**Wear protective gloves/protective clothing/eye protection/face protection.**If swallowed: Immediately call a poison center/doctor.**Specific treatment (see on this label).**Do NOT induce vomiting.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.**Continue rinsing.**IF exposed or concerned: Get medical advice/attention.**Get medical advice/attention if you feel unwell.**Take off immediately all contaminated clothing and wash it before reuse.**If skin irritation occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**In case of fire: Use for extinction: CO2, powder or water spray.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/17/2021

Reviewed on 10/17/2021

Trade name: E-Benzen

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
71-43-2 benzene
- **Identification number(s)**
- **EC number:** 200-753-7
- **Index number:** 601-020-00-8

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/17/2021

Reviewed on 10/17/2021

Trade name: E-Benzen

(Contd. of page 3)

- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

52 ppm

· PAC-2:

800 ppm

· PAC-3:

4000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

US

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/17/2021

Reviewed on 10/17/2021

Trade name: E-Benzen

(Contd. of page 4)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

71-43-2 benzene

PEL Short-term value: 15* mg/m³, 5* ppm
Long-term value: 3* mg/m³, 1* ppm
*table Z-2 for exclusions in 29CFR1910.1028(d)

REL Short-term value: 1 ppm
Long-term value: 0.1 ppm
See Pocket Guide App. A

TLV Short-term value: 8 mg/m³, 2.5 ppm
Long-term value: 1.6 mg/m³, 0.5 ppm
Skin; BEI

· **Ingredients with biological limit values:**

71-43-2 benzene

BEI 25 µg/g creatinine
Medium: urine
Time: end of shift
Parameter: S-Phenylmercapturic acid (background)

500 µg/g creatinine
Medium: urine
Time: end of shift
Parameter: t,t-Muconic acid (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/17/2021

Reviewed on 10/17/2021

Trade name: E-Benzen

(Contd. of page 5)

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Color:	Colorless
Odor:	Aromatic
Odor threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	6 °C (42.8 °F)
Boiling point/Boiling range:	80 °C (176 °F)

- **Flash point:** -11 °C (12.2 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 555 °C (1,031 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Not determined.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

Lower:	1.2 Vol %
Upper:	8 Vol %

- **Vapor pressure at 20 °C (68 °F):** 100 hPa (75 mm Hg)

- **Density at 20 °C (68 °F):** >0.88 g/cm³ (>7.3436 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

Water at 20 °C (68 °F): 0.7 g/l

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic at 20 °C (68 °F):	0.66 mPas
Kinematic:	Not determined.
Organic solvents:	<100.0 %

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/17/2021

Reviewed on 10/17/2021

Trade name: E-Benzen

(Contd. of page 6)

VOC content: <100.00 %
>880.0 g/l / >7.34 lb/gl

Solids content: >0.0 %
· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	>4,894 mg/kg (rat)
Dermal	LD50	>48 mg/kg (mouse)

71-43-2 benzene

Oral	LD50	4,894 mg/kg (rat)
Dermal	LD50	48 mg/kg (mouse)
Inhalative	LC50/4 h	9,980 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:** Danger through skin absorption.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

I

· **NTP (National Toxicology Program)**

K

· **OSHA-Ca (Occupational Safety & Health Administration)**

Substance is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/17/2021

Reviewed on 10/17/2021

Trade name: E-Benzen



(Contd. of page 7)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Assessment by list): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

14 Transport information

- | | | |
|---|--|---|
| <ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA | <p style="margin-left: 20px;">UN1114</p> | |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA | <p style="margin-left: 20px;">Benzene solution
BENZENE solution</p> | |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center; margin-bottom: 10px;">  </div> <ul style="list-style-type: none"> · Class · Label | <p style="margin-left: 20px;">3 Flammable liquids
3</p> |
| <ul style="list-style-type: none"> · IMDG, IATA | <div style="text-align: center; margin-bottom: 10px;">  </div> <ul style="list-style-type: none"> · Class · Label | <p style="margin-left: 20px;">3 Flammable liquids
3</p> |
| <ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA | <p style="margin-left: 20px;">II</p> | |
| <ul style="list-style-type: none"> · Environmental hazards: | <p style="margin-left: 20px;">Not applicable.</p> | |

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/17/2021

Reviewed on 10/17/2021

Trade name: E-Benzen

(Contd. of page 8)

· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Stowage Category	B
· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1114 BENZENE SOLUTION, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):
--

Substance is not listed.

· Section 313 (Specific toxic chemical listings):
--

Substance is listed.

· TSCA (Toxic Substances Control Act):

Substance is listed.

· Proposition 65

· Chemicals known to cause cancer:

Substance is listed.

· Chemicals known to cause reproductive toxicity for females:
--

Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:
--

Substance is listed.

· Chemicals known to cause developmental toxicity:

Substance is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)
--

A, K/L

· TLV (Threshold Limit Value established by ACGIH)

AI

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/17/2021

Reviewed on 10/17/2021

Trade name: E-Benzen

(Contd. of page 9)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is listed.

· **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS06 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

benzene

· **Hazard statements**

Highly flammable liquid and vapor.

Fatal in contact with skin.

Causes skin irritation.

Causes serious eye irritation.

May cause genetic defects.

May cause cancer.

Causes damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/17/2021

Reviewed on 10/17/2021

Trade name: E-Benzen

(Contd. of page 10)

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**
Carcinogenic hazardous material group I (extremely dangerous).
Carcinogenic hazardous material group II (very dangerous).
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**
Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** *Product safety department.*
- **Contact:**
 -
 WWW.ENERGYSEMNAS.COM
- **Date of preparation / last revision** 10/17/2021 / -
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 1: Acute toxicity – Category 1
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Muta. 1B: Germ cell mutagenicity – Category 1B
Carc. 1A: Carcinogenicity – Category 1A
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1

US